

### Lightweight Dual Motor Desk Frame

#### **General Features**

#### Max. load Constant speed

Weight of package

Standby power Accessories 100kg (per frame) 2-Stage Column: 30mm/s; 3-Stage Column: 33mm/s Box 1 (Frame 1): 23kg Box 2 (Frame 2): 23kg Box 3 (side beams): 8kg < 0.1W USB Chargers (TFA1/TFA3/TFA6), Anti-Collision Sensor (TCS1), Wireless Chargers (TWC)

Unique lightweight frame design Light in weight, solid in structure Pre-assembled frame kit – Quick and effortless assembly





RAL9006




RAL9022





\*For more color options, please consult your sales representative.

#### Dimension



Frame & Work Surface							
Frame Type	Frame dimensions (mm)	Recommended work surface dimensions (mm)					
	Width (mm)	Width (mm)	Depth (mm)				
Normal	946~1546	1000~1600	600~800				
Extended	1040~1740	1100~1800	600~800				

#### Hight Range


Column type	Frame height (mm)	Stroke (mm)	Stroke (mm)	
3-Stage	630~1280	650		
3-Stage (M)	600~1260	660		
3-Stage (S)	560~1220	660		
2-Stage	680~1180	500		






#### Side Beam

1 = One side bracket welded











#### End Pipe




Style A (for fixed tabletop)
















## BP-TEKaiir Ordering Key



Version: 20241007-D

#### **BP-TEKaiir**

<b>TL Model</b> See page 4	01MS = TEL01-MS 02MS = TEL02-MS	03MS = TEL03-MS 04MS = TEL04-MS	S 05MS = TEL05-MS 06MS = TEL0	D6-MS 07MS = TEL07-MS 10MS = TEL10-MS	
TC Model	0 = Without	1 = TC15S (Quick Release version)			
Hand Control	See page 6-7				
Color	1 = Black (RAL 9005)	2 = White (RAL 9016)	3 = Grey (RAL 9006)	4 = Special grey (RAL 9022)	
Foot	0 = Big shoe (requires column with extended outer tube), standard 2 = Foot cap + Big shoe		3 = Small shoe (requires column with extended outer tube), for rectangular column		
End Pipe (mm) See page 5	1 = Style A, fixation holes, fixed with desk fr	ame, E1 & E2: 550 (TEKaiir only)			
Desk Frame (mm)	1 = Normal, W: 946-1546	2 = Extended, W: 1040-1740			
Side Beam	See page 3				
Middle Beam	0 = Without				
Assembly Manual	0 = Without C = Chinese, TiMOTION logo, Black/White printing	E = English, TiMOTION logo, Black/White printing 1 = Chinese, TiMOTION logo, colour printi	2 = English, TiMOTION logo, colour p 3 = Chinese, No logo, Black/White p 4 = English, No logo, Black/White pr	rinting 6 = English, No logo, colour printing	

#### Terms of Use

The user is responsible for determining the suitability of TiMOTION products for a specific application. TiMOTION products are subject to change without prior notice.